

# AU-M02

A  
U  
M



A


U


M

+

+


+






5  
 1  
6  
2  
7  
 3  
 4  
 5  
 6  
 7  
3  
7  
5  
 1  
 2  
 3  
 4  
 5  
 6  
 7  
 8  
 9  
 10  
 11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100







00000000000000000000000000

1) LED0000000000000000 000000AA / AAA0000000000000000

2) 00000000000000 00000000000000

0000000000000000000000000000 00ABS material.The0000000000000000000000000000000000 000000

protection.It

3

- UP-
- 
- 
- 
- CE EN166



# HELMETS

**AU-M02**  
Safety helmet | 375g | EN 397 | ANSI

Safety helmet is well ventilated with PP shell and 4 point webbing suspension system. The helmet comes with 4 clips carrying external headlamps, a new Up-N-Down size adjustment system with a central ratchet wheel and two lateral finger push winglets for an ultimate fit.  
ATTENTION: as a polypropylene material, it is a MOQ requirement to custom your own color, however, there is nine fashion color available for you.

- WHITE
- RED
- YELLOW
- ORANGE
- GREEN
- BLUE
- BLACK
- GREY
- PINK



**Safety helmet**  
Work at height | electrician | intakes

The helmet comes with ten air intakes which provide efficient cooling and ventilation. The air intakes on the outer shell is equipped with protective aluminum anti-intrusion grille that prevents entry of debris into the helmet. If for electrician who want to have an insulation protection function, the material of intakes could be changed into nylon.

Intakes material:  
Aluminum  
Nylon

**Helmet specification**  
 Norm: EN 397  
 Outer shell: PP, Polypropylene  
 Size: universal 51-62cm headform  
 Weight: (without ear defenders or visor):375g  
 Attachment of headlamps: nylon clips  
 Color: white/red/yellow/orange/green/blue/black/grey/pink

PP 4 4  
-N - 2  
YELLOW GREY 10  
- GREY











## New visor arrives !

Hello, my dear friends, our visor is coming finally after our half years development ! come and have it. i believe you will be surprised when you get it, go go go !

ANTI - FOG  
ANTI - SCRATCH



Two colors:  
smoke, clear



CAVING



MODEL : 3A



Lighting performance

Light source	Lighting modes	Brightness	Intensity	Distance	Burn time
white	High	168 lm for 30 h	4270 cd	110 m for 30 h	30 h
	Mid	76 lm for 55 h	1970 cd	65 m for 55 h	55 h
	Low	11 lm for 120 h	310 cd	9 m for 120 h	120 h
	S.O.S	17 lm	n/a	n/a	n/a
red	High	n/a	n/a	8 m for 80 h	80 h
	Strobe	n/a	n/a	n/a	n/a

\*\*\*All above data tested for 100% real & accuracy



MODEL : 1A



Lighting performance

Light source	Lighting modes	Brightness	Intensity	Distance	Burn time
white	High	100 lm for 8 h	850 cd	95 m for 8 h	8 h
	Mid	40 lm for 13 h	280 cd	45 m for 13 h	13 h
	Low	6 lm for 38 h	55 cd	6 m for 38 h	38 h
	S.O.S	10 lm for 80 h	n/a	n/a	80 h
red	High	4 lm	n/a	5 m for 18 h	18 h
	Strobe	n/a	n/a	n/a	40 h

\*\*\*All above data tested for 100% real & accuracy

Battery Replacement MODEL : 3A

Step 1 Undone the plastic button on the light head  
Step 2 Open the battery case as picture shown



Step 3 Note the "+" and "-" of battery



Step 5 Put the battery as the picture shown



Step 4 3 AAA dry battery or rechargeable battery



Step 6 Fasten battery case



Battery Replacement MODEL : 1A

Step 1 Undone the plastic button on the light head  
Step 2 Open the battery case as picture shown



Step 3 Note the "+" and "-" of battery



Step 5 Put the battery as the picture shown



Step 4 1 AA dry battery or rechargeable battery



Step 6 Fasten battery case



condierably





**CERTIFICATE**



□□□□□□□□□□□□□□□□ □□○□□□□□

□□□□□□□□ → PC□□□□□□□□□□ → PC□□□□□□□□□□ → □□□□□□□□□□ → □□□□□□□□□□EPS□□ → □□□□□□□□□□EPS□□□□□ → □□□□□  
 □□□□□□□□□□□□□□ → □□□□□□□□□□ → □□□□□□□□□□ → □□□□□□□□□□ → □□□□□□□□□□□□□□ → IQC□□ → □□□□□□□□ → □□□□□□□□□□  
 □□□□□□□□ → □□□□□□□□□□□□□□ → □□□□□□□□ → □□□□□□□□ → □□ → □□ → □□□□□□□□□□□□□□□□