















Packaging

9 pc/box
 Dimensions: 68 * 32 * 54 CM
 Weight: 4.80 kg
 1pc/box wth 9 pc

Material:

headform:

Standard headform used for testing.

headform:

Standard headform used for testing.

headform:

Standard headform used for testing. conditioner

CERTIFICATE / AUTHENTICATION



XXXXXXXXXXXXXXXXXXXXXXXXXXXX:

XXXXXXXXXX → PC XXXXXXXXXXXX → PC XXXXXXXXXXXX → XXXXXXXXXXXXXXXX → EPS XXXXXXXXXXXXXXXX → XXXXXX EPS → XXXXXXXXXXXX
 XXXXXXXX → XXX → XXXX → XXXXXXXXXXXX → XXXXXXXXXXXXXXXXXXXXXXXX → IQC XX → XXXXXXXXXXXX → XXXXXXXXXXXXXXXX → XXXXXXXX
 XXXXXXXXXXXX → XXXXXXXX → XXXXXXXXXXXX → XX → XX → XXXXXXXXXXXXXXXXXXXXXXXX



XXXXXXXXXXXXXXXXXXXX?

XXXXXXXXXXXXXXXX:

XX: XXXXXXXXXXXXXXXX

oem XXX odm: XXXXXXXXXXXX oem XXX odm XXXXXXXXXXXXXXXX

XXXXXXXXXX: XXXXXXXXXXXXXXXXXXXXXXXX

XX: XXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXX

XX: XXXXXXXXXXXXXXXXXXXXXXXX

XXXX: XXXXXXXXXXXXXXXXXXXXXXXX



QUALITY

With strict quality management system and first-class products



OEM&ODM

We can provide OEM and ODM service for customers



R&D TEAM

With professional and strong technical development team



PRICE

We have our own production line, to reduce the price to a minimum



PATENT

We constantly introduce patented technology products



SERVICE

Perfect after-sales service, so customer satisfaction

24h service, 3d delivery

Turn your idea into a custom concrete product!



R&D Capability

