[illegible]*LED*[illegible]*AU-R2*

[illegible] LED[illegible]

-3[illegible]22 [illegible]

-[illegible]LED[illegible]LED[illegible]3[illegible]
5[illegible]
[illegible]1.5H[illegible]20[illegible] [illegible]LED[illegible]
-[illegible] [illegible]EPS[illegible]PC[illegible]
--360°[illegible]
-[illegible]CE EN1078

LED[illegible]

[illegible]	AU-R2 LED[illegible]

□□□	EPS + PC
□□□□□□□	□□□EPS□□□□□□□□□
□□□□□	PC□□□□□□□□□□□□□
□□□	EPS + PC□LED□□□□□□□□□□□□□□□
□□□□	22
□□	PANTONE
□□	M 55-58cm□L 58-61cm
□□□□□	250g
□□□□□□	7□
□□□□□□□□	1. PP□□□□PE□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 2.□□□□□□□□□
□□□□	□□□□□□□□□□□□□□
□□□	CE EN 1078LED□□□□□□□□

LED□□□□□□□□□□

LED□□□	20□□□□□□□LED□□□
□□□□	3□□□□□□□□□□□□□
□□□	□□□□□□□□2□□□□□□□□0.5□□□□□□□□□□□
□□□□□	□□□□USB
□□□□□□□□	DC 5V / 0.5A
□□□□□□□	700mAH□□□□□□□□□□□□
□□□□	□1.5□□
□□□□□□□□□	□□5□□□□□□□□□□□20□□
□□□□□□□□	290 * 215 * 150mm

□□□□□□□ *LED*□□□□□□□□□

MJ

[illegible]

[illegible]4[illegible]

-[illegible]ITW[illegible]
-[illegible]
-[illegible]
[illegible]
-Fidlock[illegible]

[illegible]

-[illegible]
-[illegible]
-[illegible]

[illegible] 23[illegible]Y[illegible]

[illegible]LED[illegible]1[illegible]

[illegible]

EVA[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]



Helmet Shape 101
European Headform
An Oval shaped helmet is designed for a rider's head with a dimension which is considerably fit for Europeans.
Generic headform
A generic headform helmet is designed for a rider's head with a dimension which is slightly longer front-to-back than its side-to-side measurement.
Asian headform
A Round shaped helmet is designed for a rider's head with a dimension which is condierably fit for Asians.

[illegible]

[illegible]

□□□

□□□□□□□□□□□□□□□□□□ISO9001□□□□□CE□□

CERTIFICATE