EN166 EN174

CE Certificated

Color：Clear

Weight：65g

□□□□□□□□□□□□□□:

AU-M2□□□□□□□□□□□□□□

6

3
-
3
5
d
b

n
n
n

p
c

□□□

4
7

g

(

)
1

c
e

3

7

i

t

w

i

t

w

1
.
P
P

□□
□□
□□

-□□□

QUICK-RELEASE RATCHET ADJUSTER

New and proprietary Up-N-Down size adjustment system provides the most precise and comfortable fit.

COMFORTABLE RAPID ABSORPTION ANTIBACTERIAL POLYESTER INNER PADS

Polyester provides greater freshness,odor elimination, integrity and preservation of material,and reduction of washing frequency.

LED HEADLIGHT
PLASTIC CLIPS FOR LED HEADLAMP
ABS material, very easy to hold the lamp.

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□:

□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□:

□□□□□□ Headform:

□□□□□□□□□□□□□□□□

□□:

□□□□□□□□□□□□□: □□□□iso 9001□□□□□□CE □□□□□□□□□□□□□□

CERTIFICATE

□□□□□□□□□□□□□:

□□□□□□□□□□□□

CUSTOMIZE FOR BRAND

□□□□□□□□□□□□□ □□i/ow:

□□□□□□□□□ → PC □□□□□□□□□□□ → PC □□□□□□□□ → □□□□□□□□□□ → □□□□□□□□□ EPS □□ → EPS □□□□□□□□□□□□ → □□□□□□□□ □□□□□□□□□□□□ → □□□□□□□□□□ → □□□□□□□□□□□□ → □□□□□□□□□□□ → □□□□□□□□□□ → IQC □□ → □□□□□□□□ → □□□□□□□□□□ □ → □□□□□□□□□□□□□□□□□ → □□□□□ →□□□□□□□□ → □□ → □□ → □□□□□□□□□□□□□□□□□□□

Production Procedure
AURORA
1
Silk screen
2
PC blister tooling
3
PC blister manufacture
4
Trmming dug hole
5
Eps raw material by different density
6
EPS in-mold tooling
7
Helmet in-mold workshop
8
In-mold machines
9
In-mold tooling
10
In-mold producing process
11
semi-finished In-mold helmet
12
IQC inspection
13
Helmet grinding
14
Inner padding production
15
Plastic injection workshop
16
Assembly line
17
Inside labeling
18
Packing
19
Warehourse
20
Installed counters

□□□□□□□□:

□□□□□□□□□□□□□ & □□□□□□□□□□□□□□□□□□□□□□□□□□□!□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ & □□□□□□□□□□□□□□□□□□□□□□□□□□□!□□□□□□□□□□□□□□□□□□□

SHIPPING

□□□□□:

> > > □□□□□□□□□□

> > > □□□ EPS □□

> > > □□□□□□□□□□□□□□□