□□□ - □□□ □□ □□ □□□, □□□□□ □□ □□ □□.

□□ □□ --- □□ □□ □□

□□ □□

□□ □□□ □□□ □□ □□ □□□ 2012 □□ 22 □ □□□ □□□ □□□□.

□□ □□□ □□□ □□ □□□ □□□ □□.

□□□ □□, □□□□ □□, □□ □□□ □□□ □□□ □□ □ □□ □□ □□□ □□ □ □□□□.
OEM □ ODM □□□ □□□. □□□ □□ □ R & A, D □□ □□ □□□ □□ □ □□ □□□□ □□□□□.
99 %□ □□ □ □□□ □□ □□□ □□, □□, □□, □□ □□□
□□□ □□□ □□ □□□□ □□□ □□□ □□ □□□ □□□□ □□ □□□ □□ □□□□.
□□□ □□□□ □□□ □□ □ □□□ □□ □□□ □□.

HELMETS

Nine color ways

AU-MO2

Safety helmet | 375g | EN 397 | ANSI

Safety helmet is well ventilated with PP shell and 4 point webbing suspension system. The helmet comes with 4 clips carrying external headlamps, a new Up-N-Down size adjustment system with a central ratchet wheel and two lateral finger push winglets for an ultimate fit.
ATTENTION: as a polypropylene material, it is a MOQ requirement to custom your own color, however, there is nine fashion color available for you.

WHITE
RED
YELLOW
ORANGE
GREEN
BLUE
BLACK
GREY
PINK

Safety helmet

Work at height | electrician | intakes

The helmet comes with ten air intakes which provide efficient cooling and ventilation. The air intakes on the outer shell is equipped with protective aluminum anti-intrusion grille that prevents entry of debris into the helmet. If for electrician who want to have an insulation protection function, the material of intakes could be changed into nylon.

Intakes material:
Aluminum
Nylon

Helmet specification

Norm: EN 397
Outer shell: PP, Polypropylene
Size: universal 51-62cm headform
Weight: (without ear defenders or visor):375g
Attachment of headlamps: nylon clips
Color: white/red/yellow/orange/green/blue/black/grey/pink

SAFETY HELMET

Helmet accessories available

Safety helmet with LED light.

AU-M02 white
Red
Yellow
Orange
Blue
Green
black
Led light headlamp led light

Safety helmet with ear protection and mesh faceshield
AU-M02 white
Red
Yellow
Orange
Blue
Green
black
earmuff good sound insulation
faceshield iron mesh

Safety helmet with plastic visor
The set is compatible with our special visor and earmuff.
AU-M02 white
Red
Yellow
Orange
Blue
Green
black
Visor plastic with eye protection
earmuff good sound insulation

□□ □□ □□ □□.

□□ □□	AU-M02 □□ □□ □□
□□:	PP □□□□
□□ □□ :	PU □□ □□, □□□ □□ □□□□ □□□
□□ □□ :	ABS / PP □
□□□	PE □□□□□
□□ □□	51-62cm
□□	375g (□ muffs□ □□□□ □□□□)
□□ □□ □□□	□□ □□□ 6.6 □□ □□
□□ □□□ □□ □□	□□, □□□, □□□ □□, □□□, □□ □□, □□
□□ □□:	□□
□□:	397 □□□□ □□□ □□□ □□ CPSC / CE □□ □□
□□□ □□ :	□□ □□ □□, □□ □□
□□ :	□□ □□
□□□:	□□ □□ □□□ □□
□:	PANTONE

OEM□ REQ□ MOQ	2000 PCS
□□ □□	□□
□□ □□ □□	□□□ □□□ □□ □□ □ □□□□□□□ □
□□ □□ □□	1. PP □□, PE □□, □□ □□, □□ □□ □ □□□ □□ □□□□ □□□□□. 2. □□ □□ □□
□□ □□	T / T, □□□ □□□
□□ □□	600,000pcs / □
□□ □□	□□, □□, □□□
□□□ □□ □□ □□ :	CE EN397, CE□ EN12492
□□□ □ :	□□□ □□□ 1. □□ □□ 2. □□ □□□ □ □□ □□□ □□ 3. □□ □□ 4. □□□□ □ □□ □□ □□ 5. □□ □□ □□ 6. □□.

□□ □□ □□□ □□ □□.

SLOT FOR EARMUFF AND MASK

CE standard ear protector ,NRR 28DB
Stainless mesh face shield
Full face protection

MICRO DIAL ADJUSTMENT

Quick release headring system,
made by Nylon material.

QUICK-RELEASE RATCHET ADJUSTER

New and proprietary Up-N-Down size adjustment system provides the most precise and comfortable fit.



GETTING THE RIGHT FIT

The headform was made according to ISO/DIS 6220 standard, and keeps 90% fitting rate.

□□ Headform

□□ ISO / DIS 6220 □□□ □□ □□□ □□□ □□□□ □□ □□□ 22 □ □□ □□□□ □□ □□□ LIMAR, SCOTT□□ □□ □□ □ □□ □□□, □□□ □ .. □, 100□ 80 □ □□□ □□ □ □□□ headform, □□ 100□ 90 □ □□□ □□□□ □□□ headform□ □□ □ □ □□□□.

□□ SAFETY □□□ □□ □□ EN397 □□□ □□

Helmet Shape 101

European Headform

A long Oval shaped helmet is designed for a rider's head with a dimension which is considerably longer front-to-back than its side-to-side measurement.

Intermediate Oval

An intermediate Oval shaped helmet is designed for a rider's head with a dimension which is slightly longer front-to-back than its side-to-side measurement.

Asian head form

A Round Oval shaped helmet is designed for a rider's head with a dimension which has an equally long front-to-back measurement as side-to-side measurement.

Packaging

18pcs/ctn

color box:26*21.5*11.5cm

mastercarton: 80*45*44CM

20ft Loadability：2500pcs

The pack box was designed especially for safety helmet which can be greatly to save the space and protect the helmet.

□□□ QC / QA □□□

Strictly QC before shipment

PRO. Q.C. SYSTEMS
Asia – Europe – America

e-mail: technical@proqc.com.hk
http://www.proqc.info

Final Inspection Report **No.: GZHG1302003863CE**

RESULTS			
Based upon the results presented,the inspected lot is judged to have been:	**PASS**	**REJECTED**	**PENDING**
	√		

INSPECTION CHECK POINTS

	CHECK POINTS	OK	NOK	COMMENTS
1	PACKING	√		
1.1	Export carton size	√		
1.2	Export carton CBM	√		
1.3	Carton Gross Weight	√		
1.4	Carton Net Weight	√		
1.5	Quantity per export carton	√		12
1.6	Unit packing: The unit is put in a pp bag and then packed in the color box.	√		
1.7	Color box printing: with logo	√		
	Model number	√		
	Product feature in Italian/Spanish/English	√		
	CE mark	√		
	Warning mark	√		
	Manual	√		
	Made in China label	√		
	EAN barcode.	√		
	Is a barcode scanner available? (YES/NO)	√		
	Rating labels stuck on the unit	√		
	Production date on the EPS liner	√		

Aurora
http://www.aurorasport.com

□□ □□□ □

INNER HOUSE TESTING

"Testing Procedures"

The Impact force detected



Field of Vision Testing

Every manufacturing steps at AURORA follows adhere to strict quality parameters and focus on quality throughout the each stagesinvolved. All raw material and semi finished goods at AURORA pass strict quality control.
The finished product, helmets at Aurora is then tested and qualified to export to the world.

Static Stability Testing

Head type detection


Head Circumference Testing

Conditioning Tests

Shock Absorbing Capacity

dynamic strength test

SHIPPING

[illegible]!