

3
3
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

Muffs



5

4

3

2

1

3

7

5

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

3

2

1

- 符合 CE EN166, 符合 - 符合, 符合 - 符合.
- 符合 CE EN166, 符合 - 符合, 符合 - 符合.
- 符合 CE EN166, 符合 - 符合, 符合 - 符合.
- 符合 CE EN166, 符合 - 符合, 符合 - 符合.

符合 CE EN166, 符合 - 符合, 符合 - 符合.



Nine color ways



HELMETS

AU-M02
Safety helmet | 375g | EN 397 | ANSI

Safety helmet is well ventilated with PP shell and 4 point webbing suspension system. The helmet comes with 4 clips carrying external headlamps, a new Up-N-Down size adjustment system with a central ratchet wheel and two lateral finger push winglets for an ultimate fit.
ATTENTION: as a polypropylene material, it is a MOQ requirement to custom your own color, however, there is nine fashion color available for you.

- WHITE
- RED
- YELLOW
- ORANGE
- GREEN
- BLUE
- BLACK
- GREY
- PINK



Safety helmet
Work at height | electrician | intakes

The helmet comes with ten air intakes which provide efficient cooling and ventilation. The air intakes on the outer shell is equipped with protective aluminum anti-intrusion grille that prevents entry of debris into the helmet. If for electrician who want to have an insulation protection function, the material of intakes could be changed into nylon.

Intakes material:
Aluminum
Nylon

Helmet specification
Norm: EN 397
Outer shell: PP, Polypropylene
Size: universal 51-62cm headform
Weight: (without ear defenders or visor):375g
Attachment of headlamps: nylon clips
Color: white/red/yellow/orange/green/blue/black/grey/pink

符合 CE EN166, 符合 - 符合, 符合 - 符合. 符合 CE EN166, 符合 - 符合, 符合 - 符合. 符合 CE EN166, 符合 - 符合, 符合 - 符合. 符合 CE EN166, 符合 - 符合, 符合 - 符合.



Comfortable fit with various heads



VERY GOOD!!



Helmet Shape 101

QUICK-RELEASE RATCHET ADJUSTER

New and proprietary Up-N-Down size adjustment system provides the most precise and comfortable fit.



European Headform

An Oval shaped helmet is designed for a rider's head with a dimension which is considerably fit for Europeans.

Generic headform

A generic headform helmet is designed for a rider's head with a dimension which is slightly longer front-to-back than its side-to-side measurement.

Asian headform

A Round shaped helmet is designed for a rider's head with a dimension which is considerably fit for Asians.

□□□ □□□ □□□ □□□:

□ □□□ □□ □□, □□ □ □□ □□-N-□□□□ □□ □□ □□□□ □□ □□□□ □□□□ □□□□□□.



Accessories



EARMUFF

The durable shell of earmuff is made out of high impact resistant ABS material. The extra soft ear cushions provide you maximum seal, comfort and complete hearing protection. It is suitable for people who work in the high noisy workplace.

Conform to the standard :
 CE EN 352-3:2002.
Certified by:
INSPEC CE 0194



FACE SHIELD

this face shield is fitted for safety helmets, and it is widely used in cutting , grinding, building and mechanical industry. the raw material with UV protection is imported from Bayer Company of Germany. 1mm and 1.5mm thickness is available for you.

Conform to the standard :
 ANSI Z87.1-2003
 CSA Z94.3-07
 CE EN 166:2002-04
Certified by:



FACE SHIELD

Iron mesh face shield provides great protection for head, face and hearing. Easy to install or install.

Conform to the standard :
 CE EN 1731:2006F
 ANSI Z87.1-2003
Certified by:

□□□ □ □□□:

□□□□ □□□□ □□ □□ □□□□ □□ □ □□ ABS □□. □□□□ □□□□ □□ □□□□ □□ □□□□ □□□□ □□ □□. □□ □□ □□ □□□□ □□□□ □□□□ □□.

FACE SHIELD:

□□□ □□ □□□ □□ □□□□ □□, □□, □□□□ □□□□ □□, □□ □□ □□. □□ □□ UV □□□□ □□□□ □□ □□□□. 1mm □ 1.5mm□ □□□ □□□ □□ □□□□ □□.

FACE SHIELD:

□ □□□ □□, □□□ □□ □□ □□□□ □□□□ □□ □□. □□ □□□□□□ □□□□□□.



New visor arrives !

Hello, my dear friends, our visor is coming finally after our half years development ! come and have it. i believe you will be surprised when you get it, go go go !

ANTI - FOG
ANTI - SCRATCH



Two colors:
smoke, clear





MODEL : 3A



Lighting performance

Light source	Lighting modes	Brightness	Intensity	Distance	Burn time
white	High	168 lm for 30 h	4270 cd	110 m for 30 h	30 h
	Mid	76 lm for 55 h	1970 cd	65 m for 55 h	55 h
	Low	11 lm for 120 h	310 cd	9 m for 120 h	120 h
	S.O.S	17 lm	n/a	n/a	n/a
red	High	n/a	n/a	8 m for 80 h	80 h
	Strobe	n/a	n/a	n/a	n/a

***All above data tested for 100% real & accuracy



MODEL : 1A



Lighting performance

Light source	Lighting modes	Brightness	Intensity	Distance	Burn time
white	High	100 lm for 8 h	850 cd	95 m for 8 h	8 h
	Mid	40 lm for 13 h	280 cd	45 m for 13 h	13 h
	Low	6 lm for 38 h	55 cd	6 m for 38 h	38 h
	S.O.S	10 lm for 80 h	n/a	n/a	80 h
red	High	4 lm	n/a	5 m for 18 h	18 h
	Strobe	n/a	n/a	n/a	40 h

***All above data tested for 100% real & accuracy



CAVING

Battery Replacement MODEL : 3A

Step 1
Undo the plastic button on the light head

Step 2
Open the battery case as picture shown

Step 3
Note the "+" and "-" of battery

Step 4
3 AAA dry battery or rechargeable battery

Step 5
Put the battery as the picture shown

Step 6
Fasten battery case

Battery Replacement MODEL : 1A

Step 1
Undo the plastic button on the light head

Step 2
Open the battery case as picture shown

Step 3
Note the "+" and "-" of battery

Step 4
1 AA dry battery or rechargeable battery

Step 5
Put the battery as the picture shown

Step 6
Fasten battery case

□□□ □□ □□□ □□ □□ □□ :

□□ **Headform :**

□□□ □□□ □□□ □□ □□ □□□ □□□ □□ □□ □□□□□□ □□□□□.

□□ **headform : C**

□□ headform □□□ □□□□ □□□ □□□ □□□ □□ □ □□□ □□□□ □□ □□ □□□□□□.

□□□ **headform :**

□□□ □□□ □□□ considerably □ □□□ □□□□ □□□ □□ □□□□□□ □□□ □□ □□.

Production Procedure



Silk screen



PC blister tooling



PC blister manufacture



Trimming dug hole



Eps raw material by different density



EPS in-mold tooling



Helmet in-mold workshop



In-mold machines



In-mold tooling



In-mold producing process



semi-finished In-mold helmet



IQC inspection



Helmet grinding



Inner padding production



Plastic injection workshop



Assembly line



Inside labeling



Packing



Warehouse



Installed counters

□ □ □ □ :