

--- LED --- - --- EPS

EPS

- 1. PU
- 2. PU
- 3. :
- 4. + PP EPS.
- 6. : ; ;
- 7. : CE EN397 & A, EN12492
- CE AU-M02, ANSI

EPS

- 1. PP
- 2. EPS
- PA
- 4.
- 5. BTS, pipelines.tram / genertaion



Black color



White



Navy blue pantone 7689 C



Pink pantone 806



Red pantone 185 C



Lime green pantone 375 C



Yellow pantone 3965 U



Orange pantone 165 C



Grey pantone 432 C

Nine color ways



Black color



White



Navy blue pantone 7689 C



Pink pantone 806



Red pantone 185 C



Lime green pantone 375 C



Yellow pantone 3965 U



Orange pantone 165 C



Grey pantone 432 C

HELMETS

AU-M02

Safety helmet | 375g | EN 397 | ANSI

Safety helmet is well ventilated with PP shell and 4 point webbing suspension system. The helmet comes with 4 clips carrying external headlamps, a new Up-N-Down size adjustment system with a central ratchet wheel and two lateral finger push winglets for an ultimate fit.

ATTENTION: as a polypropylene material, it is a MOQ requirement to custom your own color, however, there is nine fashion color available for you.

WHITE
RED
YELLOW
ORANGE
GREEN
BLUE
BLACK
GREY
PINK



Safety helmet

Work at height | electrician | intakes

The helmet comes with ten air intakes which provide efficient cooling and ventilation. The air intakes on the outer shell is equipped with protective aluminum anti-intrusion grille that prevents entry of debris into the helmet. If for electrician who want to have an insulation protection function, the material of intakes could be changed into nylon.

Intakes material:
Aluminum
Nylon

Helmet specification

Norm: EN 397
Outer shell: PP, Polypropylene
Size: universal 51-62cm headform
Weight: (without ear defenders or visor):375g
Attachment of headlamps: nylon clips
Color: white/red/yellow/orange/green/blue/black/grey/pink

Display From Different Perspectives



□□

□	□□eature	□□ □□
1. □□ □□	□□ □□ □□	□□□□ □□ □□.
□.□□ □□	AU-M02	
3. □□	ABS □ + EPS □	□□ □□, □□□□ □ □ □ ITW □□, □□ □□ □□ □□□□, □□ □□□□ □□ □□ □□□□ □ + EPS □ □□. EPS □□ □□, EPS + PC□ inmould □□, □ □□□ □ □ □□ □ □; □ □□ □□; □□ □□ □□
4.Certificate	EN 12492	
(5).□	□□ □□ □ □□□ □□□□ □□□□ □□□□	□□ pantone □□
6.Size	M (51-62CM)	□□ □□ □□ □ □□□ □□
7.Logo	□□□□ □□, □□ □□ □, □ □□ □	
8.MOQ	(500)□	□ □□ 300PCS □□ □□
9.Carton □□	73 * 58 * 35CM	
10.Packing	12PCS	10PCS □□□□ CTN
(11).□□ □□	□□OB	
12.ShippingMethod	□□ □□ □□□□ □□	□□□□
13.Payment □□	□□□□ T / T, □□□□ □□□□, L / C	
14.Sample □□	4~7□	□□□□ □□ □□ □□□□□□ □
15.Production □□ □□	20~30□	□□□□ □□ □□ □□ □□□□ □ □, □□ □□ □□□□ □□

□□ □□□□ □□ □□ :

	□□ □□.	AU-HP1
□□	□□	ABS + PC
	□	□□□□, □□, □□□□, □□, □□, □□, □□□□..
	□□	PC
	□□□□	□□□□ □□ □□□□
	□□	□□□□ □□ □□
	□□□□	□□ □□
	□□□□	1 * AA □□□□□□ □□□□
□□ □□	□□□□	□□ XP-G (6500K)
	□□	□ * (5) mm □□□□ □□
	□□□□ LED □□	100000 □□
	□□	DC 1.5 V
	□□ □□	100lumens / 8 □□
	□□□□ □□	6 □□ / (60) □□
	□□	IPX6
	□□ □□	1.5M

<p>□□</p>	□□ □□	10 * 7 * 6 (cm) / PC
	□□ □□	40 * 11 * 30 (cm) / 25pcs
	□□ □□	41 * 44 * 32 (cm) / 100PCS
	GW (□ □□ □□)	80g-100g
	□□ □□ GW	9kg-11kg

□□□ □□ □□

□□□:

□□□□ □□ □□□□ □□ □□□□□ □ □□□□□□. □□□ □□, □□□□ □□□ □□□□ □□□□ □□. □□□ □□□ □□□□ □□□ □□□□□ □□ □□□□ □□□□□.

□□:

□□□□ □□□ □□□ (□□□□ □□ □□□□ □□)□ □□□ □□□ □□ □□□ □□ □□□ □□ □□ □□ □□ □□ □□ □□ □□ □□ □□ □□□□. □□ □□ □□□ □□ □□□□□□.

□□:

□□ □□□□ □□□□ □□□□ □□□□ □□, □□ □□ □□□ □□□ □□□□ □ □□□□. □□□□□□, □□□ □ □□ □□□□, □□ □□□ □□□□ □□□□.

□□□ :

□□□□□□□□ □□ □□ □□ □□□□ □□ □ □□□□□. □□ □□□ □ □□□□, □□□□ □□ □□ □ □□ □□ □ - □□ □□□ □□□ □□□□ □□□□□ □□□□□□. □□□ □□□ □□□□ □□ □□ □□□□ □ □□□ □□□□□□□□.

□□ □□ :

□ □□□ □□□□ □□□□ □□□ □□□□□□□□ □□□□□.

PAYMENT

- We accept T/T ,Western Union or Paypal before production
- If buyers have any problems about payment , please contact us ASAP



SHIPPING

- 3-15 working days since payment receipt (based on actual quantity)
- Tracking No. will be sent to you after delivery . And you will get every important shipping status by email.

