

□□ □□□ □□ □□□ □□□ □□, □□ □□□ □□, □□□□ □□□ □□ □□□ □□

□ □□□ □ □□□ □□□ □□ :

1. □□ □□□□ □□□ □□□□□□.
2. 3 □□ □□ □□□□ □□□□ □□ □□ □□□ □□ □□ □□□ □□□□, □□ □□□□ □□ □□□.
3. □□□ □□□□ : □□□ □□□□ □□ □ □ □□ □□□□□.
4. □ □□ □□ : □□□ □ □□□□ □□, □□ □□ □□ □ □.
5. □□□□ PC □.
6. □□ EPS □□□ □□□□ □□□□.
7. □□□ □□□□ : □□ □□□ □□ □□ □ □; □□□ □□□ □□.
8. □□ : CE-CPSC-ASTM-AS / NZS-TUV-EN1078 □□ □□□ □□ □□.

□□ □□

1. □ □□□ PC □, □□ □□□ □□ □ □□□.
 2. □□□ □□□ EPS □□, □□, □□□, □□□□ □□□ □□□□.
- □□, PA □□, □ □□ 3..
4. □□□ □□ □□ □□ □□□ □□□□.
- [D □□, 5. □□□ □□□ □ R & A□, □□ □□ □□ □□□□□.](#)

□□ □□

Display From Different Perspectives



produ

□	□□	□□ □□
1. □□ □□	□□ □□□ □□	□□□ □□, □□□ □□, □□ □□□ □□, □□ □□□ □□, □□ □□□ □□, □□□ □□□ □□ □□ □□□ manufacturer
2. □□ □□	BD02	
3. □□	PC + EPS	EPS □□ □□, EPS + PC□ inmould □□, □ □□□ □□ □□ □ □; □ □□ □□; □ □ □□ □□
4. □□□	□□□ □□□	□□ □ □□□ □□□□ □□ □□
5. □□	□□ pantone □□	□□ pantone □□
6. □□	S / M (54-58cm) M / L (58-62CM)	□□ □□ □□ □ □□□ □□
7. □□	□□	□□ □□ □□ □□□ □
8. MOQ	300PCS □□ □□ 500 □ □ □□	
9. □□ □□	73 * 58 * 35CM	
10. □□	12PCS / CTN	10PCS □□□ CTN
11. □□ □□	□□ □□	
12. □□ □□	□□ □□ □□□ □□	□□□
(13) □□ □□	□□□	T / T, □□□ □□□, L / C
(14) □□ □□	4~7□	□□□ □□ □□ □□□□ □
(15) □□ □□ □□	20~30□ □	□□ □□ □□□ □□ □, □□ □□ □□□ □□

□□□ headform □□

□□□ ISO / DIS 6220 □□□ □□ □□□, □□□ □□□□ □□□ □□□ □□□ □ ... □ LIMAR□□ □□ □□ □ □□ □□□□□ 22 □ □□ □□□□ □□ □ 95 %□ □□□ □ □□□ □□ □□□ headform□ □□.

Helmet Shape 101



European Headform

A long Oval shaped helmet is designed for a rider's head with a dimension which is considerably longer front-to-back than its side-to-side measurement.

Intermediate Oval

An intermediate Oval shaped helmet is designed for a rider's head with a dimension which is slightly longer front-to-back than its side-to-side measurement.

Asian head form

A Round Oval shaped helmet is designed for a rider's head with a dimension which has an equally long front-to-back measurement as side-to-side measurement.

“Testing Procedures”



The Impact force detected



Field of Vision Testing


Every manufacturing steps at AURORA follows adhere to strict quality parameters and focus on quality throughout the each stagesinvolved. All raw material and semi finished goods at AURORA pass strict quality control. The finished product, helmets at Aurora is then tested and qualified to export to the world.



Static Stability Testing



Head type detection



Head Circumference Testing



Conditioning Tests



Shock Absorbing Capacity



dynamic strength test

CERTIFICATE / AUTHENTICATION



□□□□

□□ □ □ □□ □□ □□□□ □□ □□ □□ □□ □□ □□.

1. OEM □□□ : □□□ □□ □ □□□□ □□ □□/□□ □□ □□□.
2. Customized □□□ (1) □□□ □□ □□ : □□□ AI □□□ □□ □ □□ □□ □□ □ □□□□.
- (2) □□□ □□ □□□ : PDF □□ □□ □□□□ □□ □□□ □□□□□.
- (3) □□□ □□ □□□□ : □ □□ □□□ □ □□ □□ □□□ □□□□.
3. □□ □□ : Constantly □□□□ □□ □□ : □□ □□, □□ □□ ...

