

QF-S713 □□ □□ □□ □□ □□ □□ □□, □ □□ □□□ □□ □□

□□:

TPU □□□□ □□□□□ □□□□. □□ PC □□□□ □□□□ □□, □□ □□, UV □□, □□ - □□ □ □□ □□□ □□ □□. □□ □□□□ □□ □□□□, □□ □□□ □□□□ □□. □□□□ □□ □□. □□□□ □□□□ □□ □□ □□□□ □□ □ □□□□□. □□□□ □□□□ □□□□ □□□□ □□ □□□□ □□□□ □□ □ □□□ □□□□ □□□□□□

□□ □□

□□ □□	
□□ □□	□□ □□, □ □□ □□□ □□ □□
□□	□□□□
□□	QF-S713
□□ □□	□□ □□
□	□□□□, □□□□ □□
□□	PC □□ + TPEE □□□□
□□	□□□□ □□ □□ □□
□□	100 % UV □□ - □□ □□ □□ □□□□ □□ □□
□□ □ □□ □□	
□□ □□ □□	□□□□ □□ □□□□□□ □□
□□ □□ □□	0~15□ □ □□□ □□
□□□□□□ □□ □□	□□ □□
□□ □□	□□□□ □□ T / T

□□ □□□□



□□

FOUR ADVANTAGES



1

Anti impact international standard

ANSI Z78.1,STD-622F,CE EN166

2

Human engineering design

TPU soft spectacles frame
VS soft silicone and soft rubber pad
Unpoisonous and antianaphylaxis

3

2.8mm thickness polycarbonate lenses glasses

4

Fashion external&Exquisite workmanship





